

TC7000

320 x 240 Radiometric Thermal Camera

INTRINSICALLY SAFE THERMAL IMAGING CAMERA

TC7000 from CorDEX Instruments









- » No waiting for hot work permits with intrinsically safe certification Zone 1 IIC T4 I/II/M2/2GD
- » Find the smallest defects with the high resolution 320 x 240 IR detector
- » Be productive with the comfortable ergonomic handle grip containing 3 AA batteries providing up to 4 hours operation





- » Link your images and data to the location using the built-in RFID tag scanner
- » Go anywhere with a rugged shock and drop tested case to IEC EN60079-11
- » Swivel the lens to minimise screen reflections and comfortably access high and low areas

- » Perform safe electrical inspections with RFID compatability to CorDEX Intelligent IR Windows
- » Make decisions in the field with all the onboard analysis features you expect from a high resolution, fully radiometric thermal imaging camera
- » Save time with a simple and intuitive joystick control





- » See hotspots easily with the clear and bright 3.2" Backlit LCD Display
- » No note taking with built-in voice annotation linked to RFID tag or CorDEX Intelligent IR Windows
- » Hotspot reporting and trending through CorDEX CONNECT™
- » Stay safe with single handed operation and wrist strap supplied











WHAT DOES INTRINSICALLY SAFE MEAN?

An intrinsically safe instrument has been designed from the ground up to use low voltage and current together with detailed electronic and mechanical design to eliminate any possibility of generating an ignition source in a hazardous (explosive) area. The instrument must be approved by a notified body to international standards such as ATEX and IECEx. The IEC standard that TC7000 complies with is IEC EN 60079 - 11.

WHAT ELSE DOES IECEX CERTIFICATION OFFER?

An instrument complying with ATEX/IECEx will have been rigorously tested not only to ensure it will not generate a spark but also that it is robust enough to maintain that integrity when impacted or subjected to extremes of temperature. An ATEX/IECEx certified instrument will of necessity be much tougher than an equivalent safe area product even if for example the IP rating is similar.

WHAT AREAS CAN I ENTER WITH AN INTRINSICALLY SAFE INSTRUMENT?

Hazardous areas must be defined by the employer into designated zones and instruments must be certified for those zones. The type of hazardous atmosphere (gas, dust, mining) must be specified and the auto ignition temperature of that Zone must be identified with instruments selected that are rated safe for that temperature.



EMPLOYER DESIGNATED ZONE



CERTIFIED PRODUCT LOGO



WHAT DOES THIS RATING MEAN?

- » TC7000 is certified Ex ib IIC T4 Gb/Db
- » Ex denotes IEC Ex certification
- » Ib denotes the protection type - intrinsically safe
- » IIC denotes the apparatus group, in and C refers to the gas group
- » T4 denotes the temperature class, in this case maximum 135°C
- Gb/Db denotes both gas and dust certified

I ALREADY HAVE A THERMAL IMAGING CAMERA, WHY DO I NEED ONE WITH **INTRINSICALLY SAFE CERTIFICATION?**

SAFETY AND COMPLIANCE - CUT OUT THE RISKS AND **DELAYS OF A HOT WORK PERMIT**

If you work in the petrochemical industry you will already be aware of the Zone 1 hazardous areas in your workplace and the restrictions on uncertified instruments. Within those areas you will want to regularly scan for hotspots in:

- » Refractory lining crackers, heaters
- » Pipe insulation, missing or damaged
- » Steam traps
- » Electrical systems and switchgear

» Explosive dust environment in

sugar, grain, chemical,

» Marine, all LNG and other

petrochemical carriers


precious metals


» Flares


- » Tank insulation and level
- » Motor bearings, gearboxes, electrical connections, shaft misalignment
- » Pipe trace heating and missing or degraded insulation
- » Pharmaceutical dust and
- foodstuff industry » Aerospace – presence of » Mining industry, coal, ore, iet fuel
 - methane presence


















There are however many other industries with hazardous (explosive) areas:



RELATED PRODUCTS



Intelligent IR Windows with built in RFID Tag.



Explosion Proof Digital Cameras for hazardous (vapour) areas.



Intrinsically Safe Ultrasonic Thickness Gauge for hazardous (vapour/dust) areas.

TRAC12ATEX0037X / IECEx TRC 12.0019X	
» Ex ib IIC T4 Gb Tamb -10°C to +40°C (Vapor) » Ex ib IIIC T200°C Db Tamb -10°C to +40°C (Dust) » Ex ib I Mb (Mining)	
Temperature Information	
-4°F to 1112°F (-20°C to +600°C)	
± 2°C or 2% of reading	
9Hz	
320 x 240 uncooled microbolometer	
50mK	
8μm to 14μm	
25° x 20.5°	
1.38 mrad	
≈ 4" (10cm)	
F 1.2	
10GB	
CDX (Radiometric) JPEG (Non-radiometric)	
YES	
 » Operates with 13.54MHz passive tags » Detection range up to 5cm (1.9in) » SupportsISO/IEC15693-2,ISO/IEC18000-3 tag formats 	
-4°F to 104°F (-20°C to +40°C)	
-40°F to +158°F (-40°C to +70°C)	
3.2" Backlit LCD	
CorDEX CONNECT (Included)	
3 x MN1500 primary cell	
Upto 4 hours	

TC7000 is supplied complete as standard with:

- » Intrinsically Safe Thermal **Imaging Camera**
- » 3 x MN1500 primary cells
- » Hard carry case

- » Wrist strap
- » Neck strap
- » USB communication wand
- » Documentation CD

Authorised distributor

Why not visit CorDEX Instruments website for the latest news and downloads and learn more about the technology CorDEX Instruments provide.



For more information and customer testimonials, contact...



Global Headquarters CorDEX Instruments Ltd Unit 1, Owens Road, Skippers Lane Industrial Estate,

Middlesbrough, Cleveland TS6 6HE Tel: +44 (0) 1642 454373 Tel USA: 1 877 836 0764 Email: sales@cord-ex.com Web: www.irwindows.com www.cordexinstruments.com

