


Proceq Ground Penetrating Radars **GP8800**

Concrete inspections and structural imaging with SFCW ground penetrating radar technology now fits at the palm of your hand



Performance

Superior depth and clarity of data thanks to the unique Swiss Made radar technology with all the frequencies you'll ever need. Immediate insights with 3D and Augmented Reality.



Versatility

Inspect with ease of use, from the tightest spots to the tallest walls to the longest streets. Superior ergonomics to tackle any challenge with comfort, without cables.



Productivity

A mobile app that lets you annotate measurements with voice, photos and comments. Generate reports and share them instantly. Access your data from anywhere, anytime.



Software / Workspace App

Measurement modes	Superline Scan (1000m / 3281 ft) Area Scan (with Flexible Grid up to 100m2 / 1076 ft2)
Review modes	Superline scan ¹ A-scan (incl. envelope) Migrated view Non-migrated view Split view ¹ Time-Slice view ² Basic 3D view AR
Advanced visualization	Time-Slice view Pro 3D view Augmented Reality (AR)
Reporting	Workspace integration Automatic Logbook SEG-Y export Instant report generation Share via URL
Export formats	JPG PNG CSV SEGY HTML
Display Unit Specs*:	Latest Apple® iPad recommended (iPad with iOS 11.0 and higher) Screen size: From 7.9" to 12.9" Resolution: Up to 2732-by-2048 Memory: Up to 2TB Weight: Down to 301 g / 10.6 oz Camera: Up to 12MP Wide and 10MP Ultra Wide Optional: USB-C, 5G, Face ID
Display Unit Sensors*:	LiDAR Scanner (optional) Three-axis gyro Accelerometer Ambient light sensor Barometer Built-in GPS/GNSS

1. GP8100 only; 2. GP8000 & GP8100 only

* Depending on iPad model



Processing Unit / Sensor

Radar technology	Stepped-frequency continuous-wave (SFCW) GPR
Modulated frequency range	400 – 6000 MHz
Penetration depth	65 cm / 25.6 in
Battery	Flight-safe, removable pack, 4x AA (NiMH)
Dimensions	8.9 x 8.9 x 7.6 cm 3.5 x 3.5 x 3 in
Weight	487 g / 17.2 oz (excl. battery pack)
Ground clearance	0 cm
Antennas	1
Antenna distance to edge	4.5 cm / 1.77 in
Special features	Wireless wheel, reconfigurable at any time without tools. Cross-polarization (trailing and side-car configurations) USB-C tethering to battery pack/power bank
Connections	WiFi (802.11n) and USB-C to display unit
Autonomy	2.5 h (up to 8 hours with off-the-shelf 10'000 mAh power bank, not included)



SWISS  MADE

Present in +100 countries, we serve inspectors and engineers all over the world with the most comprehensive range of InspectionTech solutions, combining intuitive software and Swiss-manufactured sensors.

www.screeningeagle.com

[Request a quote](#)

